



# CAM FIT™ RETENTION SYSTEM

The CAM FIT™ Retention System features adjustment straps and a MIL-DTL-32067 sheepskin chin cup that have been designed for a close, comfortable fit to the wearer's face, while the asymmetric design keeps the buckle tucked smoothly along the jaw line.

## PERFORMANCE STANDARDS

- > Compliant with ACH and ECH Static Pull Strength requirements
- > Independently tested in accordance to GL-PD-07-19 – 2007 Section 3.5.2.1, Static Pull Strength and DRAFT-ECH-ICEPG16-0001 – 2009 Section 3.6.3 Static Pull Strength

## COMPATIBILITY

- > Compatible with ACH, MICH, TC2000 series, USMC LWH and many other ballistic helmets with 4-point retention mounting holes

## FEATURES

- > BOA® Fit System stabilizes helmet weight by distributing light, even pressure around the head
- > Cam Lock sliders for one-handed adjustment and secure fit
- > Left eye dominant (LED) option available
- > 4" (100 mm) Chinstrap Extender sold separately to lengthen the chinstrap to accommodate a gas mask
- > Included hardware based on shell type; hardware kits available for standard, ECH and ARC Rail fitted helmets
- > Included hardware may not be compatible with side accessory rail systems; in these cases use original hardware or contact Team Wendy for hardware options

## WEIGHT

- > Retention Only: 87 g (0.19 lb)
- > With Hardware: 112 g (0.25 lb)

## SIZING

	SIZE 1	SIZE 2
Face Circumference (cm)	66 - 74	70 - 82 ½
Face Circumference (in)	26 - 29 M/L	27 ½ - 32 ½ XL

## COLORS

 Black (FED-STD-595C #37031)	 Coyote Brown (FED-STD-595C #20150)	 Ranger Green (Pantone 7770c)
---	---	--