



Two sets of comfort pads (thin and thick) included with both sizes for further customization

TEAM WENDY® EXFIL® BALLISTIC SL

The Team Wendy® EXFIL® Ballistic SL features a lightweight composite shell providing a 15% weight reduction over the original EXFIL® Ballistic while offering the same unique EXFIL® shell geometry for optimal fit.

PERFORMANCE STANDARDS

NIJ III-A

17gr V50 > 731 m/s

9mm BFD < 25.4 mm

ENVIRONMENTAL CONDITIONS / MIL-STD-810G METHODS

- 501.5P1 High Temperature
- > 502.5P1 Low Temperature
- 507.5 Humidity
- > 509.5 Salt Fog

- 510.5PII Blowing Sand/Dust
- > 514.6 Loose Cargo Vibration
- 500.5PI Low Pressure (Altitude)

WEIGHT

Complete system weight includes helmet shell, accessory rails, impact liner and retention system

- Size 1 | Shell: 0.685 kg (1.51 lbs) | Complete System: 1.01 kg (2.22 lbs)
- Size 2 | Shell: 0.725 kg (1.59 lbs) | Complete System: 1.05 kg (2.31 lbs)

SIZING	SIZE	SIZE
Head Circumference (cm)	52-60	58-63
Head Circumference (in)	20.5-23.5	23-24.75
Hat Size (USA)	6 %-7 ½	7 3/8-7 7/8
ACH/MICH Size Equivalent	S/M/L	L/XL



SHELL ASSEMBLY

- Ballistic Performance: NIJ Level III-A (according to NIJ STD 0106.01/0108.01)
- Fragment Performance: 17ar V50 ≥ 731 m/s (2400 ft/s)
- Backface Deformation: 9mm FMJ RN @ 365 m/s (1195 ft/s), BFD < 25.4 mm all locations</p>
- Team Wendy® EXFIL® Rail 3.0 is 25% lighter than the EXFIL® Rail 2.0, maintains mounting capabilities for all common accessories and allows integration of EXFIL® Ballistic Visor and EXFIL® Face Shield
- Wilcox® SL shroud for NVG mounts provides a 35% reduction in weight from EXFIL® Ballistic Wilcox® W shroud, maintains strength and precision of a machined aluminum insert and glass-filled polymer body; compatible with retractable lanyard system

MATERIALS

- Shell: Polyethylene and other fibers in a proprietary composite matrix
- VELCRO® USA: Loop 1100, military loop
- Hardware: Stainless steel with MIL-DTL-13924D black oxide coating
- > Side Accessory Rails: Glass-reinforced polycarbonate

LINER SYSTEM

- Three-piece Zorbium® foam impact liner with 16 individual comfort pads in two thicknesses, all Berry compliant materials
- Exceeds ACH Blunt Impact requirement per AR/ PDI0-02 16Dec'13

MATERIALS

- Zorbium®: Proprietary polyurethane impact and comfort foam also used in the standard issue U.S. Army and Marine Coros 7-Pad System
- Impact Liner: Proprietary water-resistant film and loop fabric covering
- Comfort Pads: Proprietary water-resistant film and antimicrobial wicking fabric covering

RETENTION SYSTEM

- ➤ Team Wendy® CAM FIT™ Retention with BOA® Fit System for optimized stability and fit
- Features boltless design with high-strength hook/ loop attachment, meets ACH pull strength requirements
- Cam Lock sliders for one-handed adjustment and secure fit
- Left eye dominant option available

MATERIALS

- BOA* Fit System with micro-adjustable dial, coated stainless steel cable and low friction guides
- MIL-DTL-32067 leather chin cup
- > 5/8" nylon webbing
- Acetal buckles and cams
- 500D Cordura nape pad with Zorbium® foam
- Antimicrobial wicking headband sleeves

COLORS

Black (FED-STD-595C #37031)

Coyote Brown (FED-STD-595C #20150)



Ranger Green (Pantone 7770c)

AVAILABLE ACCESSORIES

SHOCK CORD KIT INCLUDED

TEAM WENDY® EXFIL® BALLISTIC VISOR

Provides stowable ANSI/MCEP and fragmentation protection with direct rail mount

TEAM WENDY® EXFIL® BALLISTIC HELMET COVERS

Mesh and nylon spandex cover available in Black, Coyote Brown, MultiCam®, MultiCam® Alpine, Ranger Green and Wolf Gray

TEAM WENDY® EXFIL® BALLISTIC EAR COVERS

Extend NIJ III-A ballistic coverage to greater than full-cut ACH

TEAM WENDY® EXFIL® OXYGEN MASK STRAP KIT

For attachment of Airborne Systems SOLR® and PHAOS, and Cobham PHANTOM O2 masks

TEAM WENDY® EXFIL® PELTOR™ QUICK RELEASE ADAPTERS

Provides tool-free, direct rail mount of all Peltor™ ComTac™ systems

Full list of compatible accessories available on TeamWendy.com

SCAN / CLICK FOR PART NUMBERS



